

封闭清扫机 / 边角刷 Sweeper/Gutter Brush



Specification		60 " -560	66 " -560	72 " -560	72 " -670	84 " -670
Working width	mm	1524	1676	1828	1828	2130
Brush diameter	mm	560	560	560	670	670
Bucket capacity	m3	0.32	0.35	0.4	0.5	0.55
Working pressure	MPa	16	16	16	16	16
Working flow	L/mm	50-125	50-125	50-125	50-125	50-125
Weight	kg	380	420	520	590	600
Length	mm	1895	2050	2200	2200	3500
Width	mm	1350	1350	1350	1560	1560
Height	mm	620	620	620	720	720

喷淋水箱套件 Water Kit



Specification		Parameter
Volume	L	50×2
Weight	kg	38
Length	mm	440
Width	mm	140
Height	mm	1040

前进式封闭清扫机 Advancing Sweeper



Specification		72" -560	72 " -670
Working	mm	1828	1828
Brush	mm	560	670
Bucket	m3	0.4	0.5
Working	MPa	16	16
Working flow	L/mm	50-125	50-125
Weight	kg	520	590
Length	mm	2200	2200
Width	mm	1350	1560
Height	mm	620	720

破碎锤 Breaker



Specification		530	680
Operating weight	kg	120	250
Working pressure	MPa	9-12	11-14
Working flow	L/mm	25-50	40-70
打击频率	BPM	600-1100	500-900
钎杆Diameter	mm	53	68
Length	mm	570	570
Width	mm	1202	1202
Height	mm	1326	1566

铣刨机 Planer



Specification		XB450	XB600
Milling width	mm	457	610
Milling depth	mm	0-152	0-152
Cutting width	mm	457	610
Roller cutting	±°	15	15
Side shift distance	mm	660	660
Cutting edge		flush	flush
Control mode		modular control	modular control
Working pressure	MPa	21	21
Working flow	L/mm	80-150	80-150
Number of cutters	pcs	48	84
Weight	kg	630	680
Length	mm	1651	1651
Width	mm	1278	1278
Height	mm	711	711

路面切割锯 Road Cutting Saw



Specification		160	240
Depth of cut	mm	160	240
Cutting width	mm	5	5
Weight	kg	360	420
Length	mm	1660	1730
Width	mm	1150	1250
Height	mm	920	980

盘式开沟机（轮盘锯） Wheel Saw



Specification		450	600
Blade width	mm	60-100	60-100
Depth of cut	mm	450	600
Cutter Diameter	mm	1220	1525
Working pressure	MPa	16	16
Working flow	L/mm	100-125	100-125
Weight	kg	900	1050
Length	mm	1930	2185
Width	mm	1700	1700
Height	mm	2010	2060

护栏清扫机 Guardrail Cleaner



Specification		Parameter
Working width	mm	600-1200
Brush diameter	mm	2×φ530
Weight	kg	550
Length	mm	2581
Width	mm	1320
Height	mm	1308

吹风机 Blower



Specification		Parameter
Working pressure	MPa	16
Working flow	L/mm	50-100
Weight	kg	112
Length	mm	1500
Width	mm	1240
Height	mm	640

斜角清扫机 Angle Broom



Specification		72 " /560	72 " /670	84 " /670	84 " /810
Working width	mm	1828	1828	2133	2133
Brush diameter	mm	560	670	670	812
Rotating Angle	°	30	30	30	25
Working pressure	MPa	16	16	16	16-21
Working flow	L/mm	50-125	50-125	50-125	40-90
Weight	kg	340	380	420	480
Length	mm	2030	2030	2335	1780
Width	mm	1020	1020	1050	2450
Height	mm	640	740	740	900

电控斜角清扫器 Electric Control Angle Broom



Specification		68 "	84 "
Working width	mm	1727	2133
Brush diameter	mm	812	812
Rotating Angle	°	25	25
Working pressure	MPa	16-21	16-21
Working flow	L/mm	40-90	40-90
Weight	kg	420	480
Length	mm	1780	1780
Width	mm	2050	2450
Height	mm	900	900

抛雪机 Snow Blower



Specification		72 "	84 "
Working width	mm	1830	2130
Snow throwing distance	m	> 12	> 12
Working pressure	MPa	16-21	16-21
Working flow	L/mm	75-140	75-140
Weight	kg	460	510
Length	mm	1892	2197
Width	mm	1100	1100
Height	mm	1700	1700

高抛筒 High throwing snow tube



Specification		
Working height	mm	2600/2700/2900/3100
Weight	kg	150
Length	mm	2600/2700/2900/3100
Width	mm	400
Height	mm	400

除冰器 Scraper



Specification		Parameter
Deicing disc diameter	mm	457
Weight	kg	60
Length	mm	1110
Width	mm	915
Height	mm	490

推雪板 Snow Blade



铲雪斗 Snow Bucket



V 型推雪板 Snow V-Blade



震动破冰器 Drum ice machine



Specification		66 "	72 "	84 "
Working width	mm	1670	1830	2130
Rotating Angle	°	±22	±22	±22
Working	MPa	16	16	16
Weight	kg	320	350	380
Length	mm	1080	1080	1080
Width	mm	1670	1830	2130
Height	mm	790	790	790

Specification		72 "	84 "
Bucket capacity	m3	0.7	0.9
Length	mm	1828	2133
Width	mm	920	920
Height	mm	660	660
Weight	kg	410	450

Specification		84 "
Working width	mm	2130
Swing angle	°	±10
Working pressure	MPa	16
Weight	kg	340
Length	mm	1186
Width	mm	2130
Height	mm	1015

Specification		72 "	84 "
Steel Wheel	mm	1855	2134
Wheel Diameter	mm	609	609
Vibration force	kg	4000	4500
Vibration Frequency	Vpm	2600	2600
Number of blades	pcs	216	288
Working pressure	mpa	16-21	16-21
Working flow	L/mm	40-90	40-90
Weight	kg	650	750
Length	mm	2100	2300
Width	mm	1000	1000
Height	mm	800	800

撒布器 Spreader



Specification		Parameter
Volume	L	272
Spreading radius	mm	3000-6000
Working pressure	MPa	16
Weight	kg	340
Length	mm	995
Width	mm	1380
Height	mm	1269

钻孔机 Auger



Specification		3500	7000	10000
Max hole diameter	mm	500	700	900
Working flow	L/mm	50-75	55-115	70-150
Working pressure	MPa	16	16	16
Max torque	N.m	3500	7000	10000
Length	mm	1160	1160	1160
Width	mm	1050	1050	1050
Height	mm	490	490	490
Weight	kg	240	260	320

钻头 Bit



Specification		6 "	9 "	12 "	18 "	24 "	30 "
Diameter	mm	150	230	300	450	600	750
Length	mm	1000	1000	1000	1000	1000	1000
Hexagonal	mm	50.8	50.8	50.8	50.8	50.8	50.8
Center Drill Specification	mm	SB30	SB30	SB35	SB45	SB45	SB45
Weight	Kg	26	30	32	38	48	65

移树机 Tree Spade



Specification		700	1000
Tree diameter	mm	80	120
Number of blades	Pcs	4	4
Diameter of soil ball	mm	700	1000
Digging depth	mm	480	600
Weight	Kg	560	850
Length	mm	1420	1990
Width	mm	1420	2030
Height	mm	1390	1500

碎木机 Chipper



土壤调节器 Soil Conditioner



树桩铲 Stump Bucket



开沟机 Trencher



Specification		Parameter
Max crushing Diameter	mm	75
Working flow	L/mm	140
Working pressure	MPa	18-21
Weight	kg	520
Length	mm	1500
Width	mm	1800
Height	mm	1800

Specification		66 "	72 "	84 "
Working width	mm	1670	1830	2130
Rotating Angle	°	±22	±22	±22
Working	MPa	16	16	16
Weight	kg	420	550	620
Length	mm	1500	1500	1500
Width	mm	1700	1850	2150
Height	mm	600	600	600

Specification		16 '
Leading edge size	mm	406
Length	mm	930
Width	mm	1150
Height	mm	610
Weight	kg	280

Specification		900/200	1200/300	2000/150
Digging Width	mm	200	300	150-200
Digging depth	mm	900	1200	2000
Working	MPa	16	16	16
Working flow	L/mm	50-75	50-75	50-75
Length	mm	1950	3300	3300
Width	mm	1160	1265	1265
Height	mm	850	900	900
Weight	kg	320	530	730

园林整地耙 Landscape Rake



双开沟机 Double Trencher



筛铲 Rock Bucket



六向推土板 Dozer Blade



Specification		66 "	72 "	84 "
Working width	mm	1670	1830	2130
Working pressure	MPa	16	16	16
Weight	kg	570	620	690
Length	mm	1626	1626	1626
Width	mm	1820	1988	2280
Height	mm	960	960	960

Specification		1000/200
Digging Width	mm	2×200
Digging depth	mm	900-1000
Working pressure	MPa	16
Working flow	L/mm	50-75
Length	mm	1950
Width	mm	2160
Height	mm	850
Weight	kg	620

Specification		72 "	84 "
Working width	mm	1830	2130
spacing	mm	76	76
Length	mm	1350	1350
Width	mm	1830	2130
Height	mm	620	620
Weight	kg	190	210

Specification		66 "	72 "	84 "
Working width	mm	1670	1830	2130
Working height	mm	790	790	790
Working Length	mm	1080	1080	1080
Weight	kg	320	350	380
Rotating Angle	°	±22	±22	±22
Working pressure	MPa	16	16	16

推土板 Dozer Blade



Specification		66 "	72 "	84 "
Working width	mm	1670	1830	2130
Working height	mm	720	720	720
Working length	mm	970	970	970
Weight	kg	300	330	360
Rotating Angle	°	±22	±22	±22
Working	MPa	16	16	16

绿篱机 Hedge Trimmer



Specification		Parameter
Working width	mm	1320
working Rotating Angle	°	270
Working pressure	mpa	16-21
Working flow	L/mm	60-80
Weight	kg	500
Length	mm	1910
Width	mm	100
Height	mm	1100

沟底压实器 Ditch Compactor



Specification		Parameter
Steel Wheel Width	mm	60-100
Wheel Diameter	mm	600
Vibration force	kg	3540
Vibration frequency	Vpm	2600
Weight	kg	800
Length	mm	1487
Width	mm	1510
Height	mm	1194

多功能割灌机 Multi-Function



Specification		DGC-10
Cutting area	mm	600-1000
Working Rotating Angle	°	120
Number of blades	个	36
Working pressure	MPa	16-21
Working flow	L/mm	60-80
Weight	kg	680
Length	mm	2000
Width	mm	3000
Height	mm	1200

井盖铣刨机 Manhole Cover Milling Machine



Specification		Parameter
Milling Depth	mm	300
Milling Diameter	mm	1400-1800
Working flow	L/mm	140
Working pressure	MPa	18-21
Weight	kg	1500
Length	mm	2100
Width	mm	1800
Height	mm	1100

卧床松土器 Cattle in bed Ripper



Specification		Parameter
Working width	mm	1500
Working Rotating Angle	°	90
Working pressure	MPa	16
Working flow	L/mm	30-65
Weight	kg	300
Length	mm	3480
Width	mm	442
Height	mm	602

液压夯 Plate Compactor



Specification		Parameter
Working width	mm	550
Vibration force	kg	4000
Vibration frequency	Vpm	2000
Weight	kg	550
Length	mm	900
Width	mm	550
Height	mm	750

箱式推板 Dung pushing device



Specification		Parameter
Max working Width	mm	3000
Length	mm	1278
Width	mm	1754
Height	mm	795
Weight	kg	350

简易推粪机 Simple manure pushing machine



软包夹 Soft Clamp



夹包叉 Fork Clamp



草垛开垦机 Haystack Reclamation Machine



Specification		Parameter
Max working width	mm	2000
Length	mm	1400-2000
Width	mm	1554
Height	mm	500
Weight	kg	300

Specification		Parameter
Working width	mm	880
Working range	mm	119-1422
Working	mpa	16-21
Weight	kg	340
Length	mm	1211
Width	mm	1700
Height	mm	700

Specification		25	30
Working width	mm	880	950
Working range	mm	600-1800	600-2000
Working	mpa	16-21	16-21
Weight	kg	400	500
Length	mm	1618	1633
Width	mm	1860	2222
Height	mm	650	850

Specification		Parameter
Working width	mm	1780
Working	mpa	16
Weight	kg	460
Length	mm	3100
Width	mm	1860
Height	mm	760

肥料叉 Utility Fork



串杆 Bale Fork



简易开沟器 Digger



树桩打磨机 Stump Grinder



Specification		Parameter
Working width	mm	1830
fork spacing	mm	130
Length	mm	1830
Width	mm	750
Height	mm	520
Weight	kg	190

Specification		Parameter
Fork Length	mm	1300
Fork Diameter	mm	50
Length	mm	1310
Width	mm	1150
Height	mm	560
Weight	kg	90

Specification		Parameter
Working width	mm	750
Length	mm	1410
Width	mm	1154
Height	mm	856
Weight	kg	260

Specification		Parameter
Swing angle	°	±55
Maximum depth of cut	mm	200
Max cutting Diameter	mm	815
Cutter Diameter	mm	610
Working pressure	mpa	14-21
Weight	kg	240
Length	mm	1882
Width	mm	1360
Height	mm	765

后置松土器 Ripper



Specification		Parameter
Rated flux	L/mm	50-125
Working pressure	MPa	16-21
Loose soil Width	mm	1000
Tillage Depth	mm	200-400
Weight	kg	450

播种机 Seeder



Specification		Parameter
Working width	mm	1740
Volume	L	150
Length	mm	786
Width	mm	2041
Height	mm	857
Weight	kg	260

抓草斗 Grapple Rake



Specification		66 "	72 "
Working width	mm	1680	1830
Working height	mm	850	850
Working length	mm	940	940
Weight	kg	190	210
Working pressure	MPa	16	16

重型抓草叉 Heavy Grass Fork



Specification		72 "	84 "
Working width	mm	1837	2134
Working height	mm	1156	1156
Working length	mm	1026	1026
Weight	kg	340	420
Working pressure	MPa	16	16

抓木斗 Grapple Bucket



Specification		single cvcylinder	Double cvcylinder
Working width	mm	1700	1700
Working height	mm	780	780
Working length	mm	920	920
Weight	kg	270	300
Working pressure	MPa	16	16

割草机 Brush Cutter



Specification		66 "	72 "
Cutting area	mm	1680	1828
Working pressure	MPa	16	16
Working flow	L/mm	50-100	75-115
Weight	kg	680	780
Length	mm	2104	2256
Width	mm	1880	2032
Height	mm	560	560

三刀割草机 Mower



Specification		66 '
Working width	mm	1680
Working pressure	mpa	14-21
Working flow	L/mm	60-80
Weight	kg	200
Length	mm	1310
Width	mm	2098
Height	mm	530

割灌机 Brush Cutter



Specification		66 '	72 '
Working width	mm	1680	1830
Working pressure	mpa	14-21	14-21
Working flow	L/mm	60-80	60-80
Weight	kg	220	240
Length	mm	880	880
Width	mm	2200	2352
Height	mm	700	700

锯树机 Tree Saw



Specification		Parameter
Saw Diameter	mm	≤ 305
Working pressure	mpa	16
Working flow	L/mm	50-120
Weight	kg	998
Length	mm	2610
Width	mm	1260
Height	mm	1920

平地器 Land Plane



Specification		72 '
Working width	mm	1850
Working pressure	mpa	14-21
Working flow	L/mm	60-80
Weight	kg	380
Length	mm	1854
Width	mm	1254
Height	mm	612

拓荒机 Forest Mulcher



Specification		60 '	72 '	84 '
Working width	mm	1524	1680	1830
Working pressure	mpa	14-21	14-21	14-21
Working flow	L/mm	60-80	60-80	60-80
Weight	kg	1150	1250	1380
Length	mm	1447	1447	1447
Width	mm	1894	2206	2434
Height	mm	1643	1643	1643

夹树机 Tree Puller



Specification		Parameter
Working width	mm	848
Puller Diameter	mm	10-280
Working pressure	mpa	16
Working flow	L/mm	50-120
Weight	kg	380
Length	mm	1440
Width	mm	1200
Height	mm	1224

旋耕机 Soil Tiller



Specification		Parameter
Rated flux	L/mm	50-125
Working pressure	MPa	16-21
Loose soil Width	mm	1300
Rake widteh	mm	1600
Rake length	mm	700
Length	mm	890
Width	mm	1600
Height	mm	800
Weight	kg	450

铲斗 Standard Bucket



Specifcation		66 "	72 "	84 "
Bucket capacity	m3	0.45	0.5	0.6
Length	mm	1024	1024	1024
Width	mm	1722	1876	2180
Height	mm	495	495	495
Weight	kg	175	190	220

胎外链 Steel Tracks



Item	Standard	Customized
No.of sections	36	Can adding or subtracting knots
Suitable tire	10-16.5/12—16.5/14-17.5	
Suitable wheelbase	980—1080	can be adjustment by knots

组合铲 4 in 1 Bucket



Specification		60 "	66 "	72 "	84 "
Bucket capacity	m3	0.35	0.4	0.5	0.6
Length	mm	1524	1676	1828	2133
Width	mm	920	920	920	920
Height	mm	660	660	660	660
Weight	kg	340	380	410	450
Working pressure	MPa	16	16	16	16

带盖铲斗 Closed Bucket



叉铲 Pallet Fork



侧移叉铲 Side Shift Pallet Fork



筛抓 Rock Bucket Grapple



Specification		60 "	66 "	72 "	84 "
Bucket	m3	0.35	0.4	0.5	0.6
Length	mm	1524	1676	1828	2133
Width	mm	920	920	920	920
Height	mm	660	660	660	660
Weight	kg	340	380	410	450

Specification		C10	C15
Rated load	kg	1000	1500
Fork Length	mm	770	1000
Length	mm	1150	1150
Width	mm	1010	1240
Height	mm	980	980
Weight	kg	150	180

Specification		1.5T
Rated load	kg	1500
Fork Length	mm	1100
Working pressure	MPa	16-21
Working flow	L/mm	40-90
Length	mm	1518
Width	mm	1395
Height	mm	1224
Weight	kg	350

Specification		72 双缸
Working width	mm	1830
Working range	mm	300-500
Working pressure	mpa	16-21
Weight	kg	400
Length	mm	1872
Width	mm	1100
Height	mm	790

振动压路机 Vibratory Roller




平地机 Grader



搅拌机 Mixer



铲斗搅拌机 Bucket Mixer



Specification		66 "	72 "
Steel Wheel Width	mm	1670	1855
Wheel Diameter	mm	600	600
Vibration force	kg	3540	3880
Vibration frequency	Vpm	2600	2600
Weight	kg	800	900
Length	mm	1848	2000
Width	mm	900	900
Height	mm	610	610

Specification		84 "
Working width	mm	2130
Rotating Angle	°	±22
Working pressure	MPa	16
Weight	kg	760
Length	mm	1970
Width	mm	2130
Height	mm	720

Specification		100	200
Volume	m3	0.1	0.2
Rotating speed	r/min	5 ~ 30	5 ~ 30
Working pressure	MPa	16	16
Working flow	L/mm	50-100	50-100
Weight	kg	300	360
Length	mm	1200	1300
Width	mm	1160	1200
Height	mm	1100	1200

Specification		30
Bucket capacity	m ³	0.3
进料Volume	m ³	0.3
Max discharge Volume	m ³	0.3
Mixing time	≤"	50
Mixing speed	r/min	70
Working pressure	mpa	16-21
Working flow	L/min	75-140
Weight	kg	380
Length	mm	1250
Width	mm	1030
Height	mm	950

挖掘臂 Backhoe Arm



Specification		
Digging bucket Width	mm	380
Digging bucket volume	m3	0.06
Max digging depth	mm	2000
Length	mm	1770
Width	mm	1170
Height	mm	740
Weight	kg	300
Working pressure	MPa	16

回转挖掘臂 Swing Backhoe Arm



Specification		Parameter
Bucket Width	mm	380
Bucket capacity	m3	0.06
Max digging depth	mm	2000
Rotating Angle	°	110
Weight	kg	350
Working pressure	MPa	16
Length	mm	1770
Width	mm	1170
Height	mm	740

挖掘机 Backhoe



Specification		Parameter
Bucket width	mm	380
Bucket capacity	m3	0.06
Max digging depth	mm	2400
Max working Height	mm	2980
Loading Height	mm	1910
Arm Rotating Angle	°	120
Length	mm	2280
Width	mm	2200
Height	mm	2090
Weight	kg	780
Working pressure	MPa	16

高卸料铲斗 High Dump Bucket



Specification		66 "	72 "	84 "
Bucket capacity	m3	0.45	0.5	0.6
Working pressure	MPa	16	16	16
Length	mm	1024	1024	1024
Width	mm	1722	1876	2180
Height	mm	495	495	495
Weight	kg	175	190	220

弧形铲斗 Curved Bucket



Specification		66 "	72 "	84 "
Bucket capacity	m3	0.45	0.5	0.6
Length	mm	1024	1024	1024
Width	mm	1722	1876	2180
Height	mm	495	495	495
Weight	kg	175	190	220

液压绞车 Hydraulic winch



Specification		Front-mounted	Rear-mounted
Towing Weight	kg	3000-5000	2000
Working pressure	MPa	16	16
Weight	kg	200	120
Length	mm	670	500
Width	mm	1234	1092
Height	mm	735	450

旋转挂架 Tilt-TatchTM



Rotating Angle	°	±15
Weight	kg	140
Working pressure	MPa	16
Length	mm	230
Width	mm	1440
Height	mm	510

吊具 Sling



Specification		Parameter
Sling Weight	Kg	≤ 1500
Sling Diameter range	mm	1700
Weight	kg	340
Length	mm	1132-1732
Width	mm	1200
Height	mm	592

地坪打磨机 Floor Grinder



Specification		Parameter
Working width	mm	1698
Left-right swing	mm	110
Working pressure	MPa	16
Weight	kg	670
Length	mm	1326
Width	mm	1540
Height	mm	788

打桩机 Pile Driver



Specification		Parameter
Anchor Diameter	mm	100-300
Anchor Length	mm	500-2000
Rotation speed	r/min	5 ~ 30
Working pressure	MPa	16
Working flow	L/mm	50-100
Weight	kg	900
Length	mm	1500
Width	mm	1460
Height	mm	2100

后支撑装置

Rear Support



Specification		Parameter
Working pressure	MPa	16
Working flow	L/mm	50-100
Weight	kg	112
Length	mm	900
Width	mm	240
Height	mm	240