

STANDARD CONFIGURATION

Yanmar engine / Plot multiplexer / Doosan hydraulic variable plunger pump/U.S.A Eaton motor / Engineer- ing cylinder, built-in america parker seal Adjustable dozer/ Steel crawler Air conditioner I Adjustable driv- er's seat I Standard bucket/ Hydraulic lock I Cab/ Escape hammer/ Portable fire extinguisher I Audio

APPLICATION

Applicable to indoor demolition, toilet upgrading,engineering forcible entry,excavate barren hills,small earthwork,- municipal projects,break concrete,dredging river and other working

PRODUCT APPLICATION

It is used for earthwork excavation, loading, leveling, slope finishing, hoisting, breaking, demolish, and ditch excavation. Also, it is able to work for mining, or places with severe working conditions. It has the following characteristics: low production cost, less investment, and powerful outdoor operation.

OPTIONAL CONFIGURATION

Hammer / Ripper / Log grapple / RakelAuger drill Large bucket/ Mud Bucket/Air Conditioning

Excavator 08



FEATURE

- ♦ Adopt advanced constant power variable plunger pump.
- ♦ Adopt wet multi-disc brakes, with buffer control, smooth operation and braking.
- ♦ Adopting pure imported parts from South Korea, the working curve of valve stem matches the hydraulic valve.
- ♦ TEngineering cylinders, America Parker sealing ring, comes with a buffer device.
- ♦ 16MN steel plates were used and each bushing was quenched and tempered.

PERFORMANCE PARAMETER

Performance Parameters	Unit	TCE08A
Operating Weight	Kg	750
Engine Model		KOOP192F
Rated Power	Kw	8.6kw/12hp
Bucket Capacity	m ³	0.02
Bucket Width	mm	300
Max Digging Force	Kn	9.5
System Working Pressure	Mpa	16
Swing Speed	rpm	12
Traveling Speed	km/h	2
Gradeability	°	30
Ground Pressure	Kpa	20
Operating Range		
Max. Digging Distance	mm	2450
Max. Digging Depth	mm	1200
Max. Digging Height	mm	2430
Max. Dumping Height	mm	1650
Min. Turning Radius	mm	1100
Overall Dimensions		
Overall Length	mm	2200
Overall Width	mm	720
Overall Height	mm	1150
Min. Ground Clearance	mm	380
Track Ground Length	mm	1140
Track Width	mm	150

The Specification Will be changed with the technology progress and without notice.