

TDER INDUSTRIAL

xiamen tder industrial co.,ltd.

<http://www.tder-group.cn>

LOADER DETAILS



Multiple selection of engine to meet different emission standard



Sensitive articulated steering



LED light, standard protection lampshade



The user-friendly design of the cabin efficient and convenient.



Reversing camera-- Safeguard the safety of reversing

TDER LOADER

ZT930

* The specification will be changed with the technology progress and without notice.

LOADER PARAMETER

Model	ZT930
Bucket capacity	1.8 m³
Rated load	3000 kg
Overall dimension	7300*2300*3200mm
Operating weight	9700 kg
Max. dumping height	3200 mm
Max. dumping distance	1000 mm
Engine	Weichai DEUTZ
Cylinder number	6-cylinders
Rated power	92 KW (125HP)
Steering type	Full-hydraulic, articulated
Torque converter model	YJ320, automatic, hydraulic converter
Gear shift	4 forward, 2 reverse
Max. speed	39 km/h
Axle	4WD, heavy hub reduction
Tire size	17.5-25
Service brake	Gas cap oil disc brake on 4 wheels
Parking brake	Hand operated caliper disc
Operating type	Mechanical double joystick
Optional operating type	Pilot control
Optional configuration	Air conditioner, rearview camera etc.
Optional attachment	Quick hitch, fork, log grapple etc.

TDER LOADER

* Powerful engine: Weichai engine or LIJIA SL4105ABK engine, strong power, energy conservation and environmental protection. DF-Cummins engine is optional.

* Long wheel base design makes the loader more steady, high dumping height and short action cycling time makes the working more efficient



▲ ZT925