

TDER INDUSTRIAL

xiamen tder industrial co.,ltd.

<http://www.tder-group.cn>

LOADER DETAILS



Fully function panel



Sensitive articulated steering



Mutiple seletion of engine to meet different emission standard



Comfortable operating



Heavier type axle

TDER LOADER

ZT956

* The specification will be changed with the technology progress and without notice.

LOADER PARAMETER

Model	ZT956
Rated power	162KW/2200r/min
Overall dimensions	7600mm*3000mm*3380mm
Operating weight	16800KGS
Rated loading capacity	5000KGS
Bucket capacity	3m ³
Bucket width	3000mm
Wheel base	2870mm
Tread width	2250mm
Dumping height	3140mm
Dumping reach	1120mm
Turning angle	35°± 1°
Max.climbing Gradient	28°
Turning radius	6650mm
Max.breakout forth	145kN
Max.torque	745.3N.m
Lifting time	≤6.8s
Hydraulic cylinder time	≤12.55s
Specification of tire	23.5-25
Travel speed	
Forward gear I	11.5km/h
Forward gear II	38km/h
Reserve gear I	16km/h

TDER LOADER

* Four wheel double-line caliper disc braking system with a gas container in the back to guarantee a more safety and reliable operation. ROPS/FOPS cab is optional.

* The planetary transmission, superior in the efficiency delivery and overload adaption.

* Besides the special design of structure, full steel plate thickening, the thickness of lift arm and hinge plate reaches 60mm.

