

TDER INDUSTRIAL

xiamen tder industrial co.,ltd.

<http://www.tder-group.cn>

LOADER DETAILS



Fully Function Panel



Sensitive Articulated Steering



Multiple Selection Of Engine To Meet Different Emission Standard



Comfortable Operating



Heavier Type Axle

TDER LOADER

ZT966

* The specification will be changed with the technology progress and without notice.

LOADER PARAMETER

Model	ZT966
Rated power	175KW/2200r/min
Overall dimensions	8250mm*3210mm*3640mm
Operating weight	19500KGS
Rated loading capacity	6000KGS
Bucket capacity	4m ³
Bucket width	3210mm
Wheel base	3200mm
Tread width	2470mm
Dumping height	3750mm
Dumping reach	1300mm
Turning angle	35°± 1°
Max. climbing Gradient	28°
Turning radius	7470mm
Max. breakout forth	175kN
Max. torque	1000N.m
Lifting time	≤6.8s
Hydraulic cylinder time	≤10.5s
Specification of tire	26.5-25
Travel speed	
Forward gear I	11.5km/h
Forward gear II	38km/h
Reserve gear I	16km/h

TDER LOADER

- * Axle: Reinforced Q axle features larger carrying capacity and can forbid the oil leak efficiently, high reliability and convenient to maintenance.
- * Brake systems: Four wheel double-line caliper disc braking system with a gas container in the back to guarantee a more safety and reliable operation.
- * Quenched integral cutting edge bucket, more strength, better wearing resistance and long life.



▲ ZT966