



1. The appearance is simple, generous and beautiful;
2. The large-view gantry design makes the driver's vision wider;
3. Optional casting steering axle, low maintenance cost later.
4. The advanced steering wheel adjustment mechanism improves the comfort of operation and the reliability of adjustment;

产品主要参数

Model		FD30	FD35	FD38
Rated lifting load	kg	3000	3500	3800
Load center distance	mm	500		
Free lifting height	mm	160		
overall length (With fork/Without fork)	mm	3752/2682	3763/2693	3963/2893
Width	mm	1225		
Overhead guard height	mm	2090		
Wheelbase	mm	1700		
Minimum ground clearance	mm	135		
Mast tilt angle (front/rear)	%	6° /12°		
Tire no. (before)		28×9-15-14PR		
Tire no. (after)		6.5-10-10PR		
Minimum turning radius (outer side)	mm	2400	2420	2710
Minimum right angle aisle width	mm	4260	4260	4720
Fork size	mm	1070X125X45	1070X125X50	1070×150×50
maximum working speed(Full-load/No-load)	km/h	18/19	19/19	
maximum lifting speed(Full-load/No-load)	mm/s	440/480	330/370	340/380
maximum gradeability(Full-load/No-load)	%	15/20		
Forklift weight	kg	4250	4500	4800
Engine model		Quanchai4C2-50V32 / Quanchai4C2-50C41		